




Applicable Standards

- ISO 8528-5:2018
- GB/T2820.5-2009
- CE

General Information		Prime power	Standby power
Rated Power (kVA)		100	110
Power Rating (kW)		80	88
Frequency (Hz)		50	
Engine Model		NEF45TE2P	
Engine Speed (RPM)		1500	
Phase		3	
PF		0.8	
Control System		Digital	
Rated voltage (V)		400/230 (According to customer requirements)	
Fuel tank capacity operating time		≥ 8h @ 75% load	
Fuel Consumption (L/h)	110% load	20.9	
	100% load	19.2	
	75% load	15.7	
	50% load	11.3	



Dimension and Weight

Model	CPF100-1 Open type	CPF100S-1 Silent type
Length (L) mm	2350	2800
Width (W) mm	750	1130
Height (H) mm	1500	1580
Dry weight (kg)	1200	1680
Tank capacity (L)	180	280
The loading capacity (40'HC)	15 units	8 units

Note: Specifications and illustrations are subject to revision without notice.

Environmental Conditions

- Ambient temperature: ~+50°C
- Altitude: ≤1000m

Remark: If your conditions are different from the above, please contact our sales.

Factory Inspection

- Complete design and quality inspection
- 0%, 25%, 50%, 75%, 100%, 110% load test.
- Function test and Protection Test.

Painting Process

- Our Supplier has the most advanced automatic spraying/powder coating production line and is equipped with various sandblasting equipment to ensure higher quality.
- Canopy painting: Henkel pretreatment process and world-famous brand AkzoNobel powder.
- Base Frame painting: Sandblasting process and AkzoNobel powder (Hempel paint is optional).



Engine Specifications

Engine model & manufacturer		NEF45TE2P (FPT)
Emission Certification		Stage IIIA
Number of cylinders		4
Cylinder arrangement		In-line
Cycle		Four stroke
Aspiration		Turbocharged
Bore x Stroke		104 x 132 mm
Displacement		4.5 L
Compression ration		17.5: 1
Prime power /speed		91 kW/1500 rpm
Standby power /speed		100 kW/1500 rpm
Speed governor		ECU
Cooling system		Forced Water Cooling Cycle
Frequency droop		≤ 3%
Total lubrication system capacity		12.8 L
Coolant capacity (engine only)		18.5 L
Fuel consumption	100% load	210.7 g/kWh @1500 rpm
Starter motor		DC 12V
Charge alternator		DC 14V

Alternator Specifications

Alternator	
Number of phase	3
Power factor (Cos Phi)	0.8
Poles	4
Insulation type	H class
Winding Pitch	2/3
IP rating	IP23
Bearing	Single bearing
Voltage regulator	AVR
Coupling	Flexible disc

Control Panel

ComAp offers a range of controller types designed to meet various needs in the field of generator set control and monitoring. While specific models and features may vary, here are some examples of COMAP controllers commonly used:

Inteli Gen 500



- InteliGen 500 is a paralleling controller with 5" colour display for advanced diesel gen-set applications, supporting both single and multiple gen-sets running in grid-tied or island operations.
- Effective power management

- Built-in PLC interpreter
- Load shedding
- Dynamic spinning reserve
- Built-in colour display
- Automatic Mains Failure
- Mains application in a gen-set controller
- Remote connection & monitoring
- Start-up synchronization
- Droop regulation
- Peak shaving

InteliLite 4 MRS 16



- InteliLite 4 MRS 16 is an advanced single gen-set controller for prime power applications. Ensuring reliable prime power, the controller effectively monitors, protects, and controls the generator and circuit breaker to supply the load.

- Cybersecurity by design
- Easy configuration with InteliConfig
- Reliable internet access
- Built-in PLC logic
- Easy troubleshooting
- Zero power mode features to avoid battery drainage for prime power applications
- Integrated communication and control ports

InteliLite 4 AMF 25



- InteliLite 4 AMF 25 an advanced single gen-set controller for stand-by and prime power applications. Intuitive, flexible, easy to install and use, the InteliLite 4 AMF 25 controller offers multiple configuration options to create the best solution for controlling and monitoring your gen-sets both on-site and remotely.

- Flexible and efficient setup and monitoring
- Built-in PLC logic and PLC editor with easy-to-use drag and drop editing blocks
- AirGate 2.0 for easy connection to your equipment remotely
- Remote control and monitoring with Web Supervisor
- High-level security features
- Stand-by and prime power application control
- Cybersecurity by design

InteliVision 5



- InteliVision 5 is an easy-to-use industrial operator panel with a colour screen for monitoring of single gen-set for various applications. This robust and intuitive plug & play solution provides comprehensive visual overview of all engine data, monitoring information and trend history.

- Intuitive navigation
- Robust design
- Simple installation
- 5.7" Colour screen
- Plug & play solution
- Broad operating temperature range from -30°C to +70°C
- Local and remote access for single controller monitoring
- Front face is sealed to IP65

- Our expert team will assist you in selecting the appropriate ComAp controller tailored to your specific requirements, ensuring the best choice for your application. Additionally, we offer a range of controller options from other reputable brands such as Woodward, Deep Sea, and Smartgen, providing you with a wider selection to meet your needs.

Options

Engine	Alternator	Fuel System	Generating Set
☐ Water Jacket Preheater ☐ Oil Preheater ☐ Oil manual pump	☐ PMG excitation ☐ Space heater ☐ Winding temperature measuring	☐ 12 / 24 hour base tank ☐ Bunded fuel tank ☐ External fuel tank ☐ Automatic fuel feeding ☐ Switch between external tank and base tank (three-way valve)	☐ Deepsea, ComAp, Smartgen Woodward, etc. controller ☐ Trailer ☐ Tools with the machine



Proudly Distributed by

www.classpower.com.au

Photographs are for illustrative purposes only and may not reflect the final specification. All information in this document is substantially correct at time of printing and may be altered subsequently. Final weight and dimensions will depend on completed specification.